

## Technical Data Sheet

Page 1 of 1

<b>Properties:</b>	AKEMI® Primer AP 70 is a 1-component primer for AKEMI® silicones to improve adhesion.
<b>Application Area:</b>	AKEMI® Primer AP 70 is used to prime joint flanks before application of AKEMI® silicones on porous, absorbent, mineral surfaces such as concrete, tile grout, mortar or ceramic surfaces, which are under a constant exposure to wet conditions such as swimming pools, sauna or pressure vessel construction.
<b>Instructions for Use:</b>	<ol style="list-style-type: none"><li>1. Contact areas must be dry, clean and free of dust and grease.</li><li>2. Apply with a brush on clean and dry surface.</li><li>3. Protect treated surfaces against humidity and dust</li><li>4. After open time of approx. 60 minutes the silicone sealant can be applied.</li></ol>
<b>Special Notes:</b>	<ul style="list-style-type: none"><li>- In order to prevent stains do not apply primer on visible areas.</li><li>- AKEMI Primer AP 30 does not adhere on metallic or glazed surfaces such as tiles or enamel.</li><li>- Tools can be cleaned with AKEMI® Universal Diluent.</li><li>- For adequate waste disposal container must be completely emptied.</li></ul>
<b>Storage:</b>	12 months in a cool place.
<b>Health &amp; Safety:</b>	Read Material Safety Data Sheet before handling or using this product.
<b>Important Notice:</b>	The above information is based on the latest stage of development and application technology. Due to a multiplicity of different influencing factors, this information – as well as other oral or written technical advises – must be considered as non-binding hints. The user is obliged in each particular case to conduct performance tests, including but not limited to trials of the product, in an inconspicuous area or fabrication of a sample piece.

TDS 11.15